

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 02-096606

(43)Date of publication of application : 09.04.1990

(51)Int.Cl.

G01B 15/00

H01J 37/22

H01J 37/244

H01J 37/28

(21)Application number : 63-247492

(71)Applicant : CANON INC

(22)Date of filing : 03.10.1988

(72)Inventor : KORENAGA NOBUSHIGE

UZAWA SHUNICHI

GOTO SUSUMU


KARIYA TAKUO

(54) MINUTE-SIZE MEASURING APPARATUS

(57)Abstract:

PURPOSE: To obtain a measuring apparatus wherein the measuring errors of minute sizes due to temperature change in an environment and mechanical vibration by detecting the position of an electron beam in a plane perpendicular to an optical axis, and moving the electron beam from said position to a specified position.

CONSTITUTION: An electron beam mirror tube has a reference point and has electron-beam position detectors 10a and 10b which detect the position of the electron beam and electron-beam-position correcting deflection coils 6a, 7a, 6b and 7b. A length measuring device having beam splitters 19Xa and 19Xb is optically connected to the reference points of the electron-beam-position detectors 10a and 10b and the reference point of a specimen stage 17. The relative positions of the electron-beam position detectors 10a and 10b and the specimen stage 17 are determined. A central processing unit 37 is connected to the electron-beam position detectors 10a and 10b and the electron-beam-position correcting deflection coils 6a, 7a, 6b and 7b. The amount of deviation required for moving the electron beam to a specified position in a plane that is perpendicular to the optical axis of the electron beam is determined based on the detected signals of the electron-beam position detectors 10a and 10b. Deflecting signals for moving the electron beam to the specified position are imparted to the electron-beam position correcting deflection coils 6a, 7a, 6b and 7b.





(19)

(11) Publication number:

02096606 A

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **63247492**(51) Intl. Cl.: **G01B 15/00 H01J 37/22 H01J 37/244 H01J 37/28**(22) Application date: **03.10.88**

(30) Priority:	(71) Applicant: CANON INC
(43) Date of application publication: 09.04.90	(72) Inventor: KORENAGA NOBUSHIGE UZAWA SHUNICHI GOTO SUSUMU KARIYA TAKUO
(84) Designated contracting states:	(74) Representative:

**(54) MINUTE-SIZE
MEASURING APPARATUS****(57) Abstract:**

PURPOSE: To obtain a measuring apparatus wherein the measuring errors of minute sizes due to temperature change in an environment and mechanical vibration by detecting the position of an electron beam in a plane perpendicular to an optical axis, and moving the electron beam from said position to a specified position.

CONSTITUTION: An electron beam mirror tube has a reference point and has electron-beam position detectors 10a and 10b which detect the position of the electron beam and electron-beam-position correcting deflection coils 6a, 7a, 6b and 7b. A length measuring device having beam splitters 19Xa and 19Xb is optically connected to the reference points of the electron-beam-position detectors 10a and 10b and the reference point of a specimen stage 17. The relative positions of the electron-beam

position detectors 10a and 10b and the specimen stage 17 are determined. A central processing unit 37 is connected to the electron-beam position detectors 10a and 10b and the electron-beam-position correcting deflection coils 6a, 7a, 6b and 7b. The amount of deviation required for moving the electron beam to a specified position in a plane that is perpendicular to the optical axis of the electron beam is determined based on the detected signals of the electron-beam position detectors 10a and 10b. Deflecting signals for moving the electron beam to the specified position are imparted to the electron-beam position correcting deflection coils 6a, 7a, 6b and 7b.

COPYRIGHT: (C)1990,JPO&Japio

